



Façade cassettes are among the various technologies and finishing materials for the construction field, which are used to cover external walls. They are designed to combine the functional and aesthetic part of the construction.

Abkant façade cassettes - technical characteristics

Material	Pre-painted steel sheet			
Available thickness (mm)	0.60			
Steel class	minimum S250GD			
Minimum zinc coverage (g/m ²)	275			
Exterior paint coating (µm)*	SP L	SP MAT	PVDF	PUR NOVA
	25	35	25	55
RUV/RC	RUV2/RC2	RUV4/RC4	RUV4/RC4	RUV4/RC5
Total width (mm)	356			
Useful width (mm)	327			
Weight (kg/m ²)	6.1			
Minimum length (mm)	500			
Maximum length - recommended (mm)	2000			
Corrugation height (mm)	30			




The values in sections are expressed in mm.

*SP L - Glossy Polyester
SP MAT - Super Matte Polyester
PVDF - Polyvinylidene fluoride
PUR NOVA - Mat Polyurethane

Steel type and structure

Minimum steel class S250GD steel with **275 g/m²** Zinc coating, according to EN 10346 and EN 10143.



- 1 ▶ Steel
- 2 ▶ Zinc coating
- 3 ▶ Passivation coating
- 4 ▶ Primary protection coating
- 5 ▶ Exterior paint coating
- 6 ▶ Interior paint coating

- Optimized**
- Lightweight**
- Adaptable**
- Easy fitting**
- Extended lifespan**
- Sustainable**